

Specificaties 2023

zeliox®



| | Zeliox Compact | Zeliox Custom | |
|---------------------------|----------------------------------|--------------------------|--------------------------|
| Accu capaciteit | | | |
| Vermogen | 1600 Watt | 2500 Watt | 3500 Watt |
| Type | Lithium 12V | Lithium 24V | Lithium 24V |
| kWh | 1.20 kWh | 2.25 of 3.60 kWh | 2.25 of 3.60 kWh |
| Ah | 100 | 100 of 144 | 100 |
| Chemie | LifePO4 | LifePO4 | LifePO4 |
| Aansluitingen | | | |
| 230V AC invoer | Zeliox Compact power cable | Zeliox shore power cable | Zeliox shore power cable |
| 230V AC uitvoer | 1x AC power socket 1x IEC C19 | 2x AC power socket | 2x AC power socket |
| 12V DC invoer | Anderson 50A | Anderson 175A | Anderson 175A |
| 12V DC uitvoer | Anderson 50A | Anderson 50A | Anderson 50A |
| Product informatie | | | |
| Gewicht (kg) | 23 | 63 of 65 | 63 |
| Afmetingen (hxbxl mm) | 190x420x355 | 430x580x380 | 430x580x380 |
| IP Rating | IP20 | IP20 | IP20 |
| Temperatuur werkbereik | 0-50°C | 0-50°C | 0-50°C |
| Maximum temperatuur | 70°C | 70°C | 70°C |
| Koeling | geforceerde lucht | geforceerde lucht | geforceerde lucht |
| AC Invoer | | | |
| Spanning (V) | 190-260 | 190-260 | 190-260 |
| Frequentie (Hz) | 50 | 50 | 50 |
| Laadvermogen (W) | 950 | 1250 of 1500 | 1250 |
| AC Uitvoer | | | |
| Spanning (V) | 230 AC | 230 AC | 230 AC |
| Frequentie (Hz) | 50 | 50 | 50 |
| Amp limiet (A) | 10 | 10 | 10 |
| Continu (W) | 1300 | 2800 | 2800 |
| 10 minuten (W) | 1600 | 3500 | 3500 |
| 10 sec piek (W) | 2500 | 6500 | 6500 |
| DC Invoer | | | |
| Spanning (V) | 12-15 DC | 12-15 DC | 12-15 DC |
| Continue stroom (A) | 30 | 60 | 60 |
| DC Uitvoer | | | |
| Spanning (V) | 12 | 12 | 12 |
| Amp limiet (A) | 25 | 25 | 25 |
| Continu (W) | 300 | 300 | 300 |
| Continue stroom (W) | 25 | 25 | 25 |
| Maximum stroom (W) | 35 | 35 | 35 |