



	ZelioX Compact	ZelioX Custom	ZelioX Custom	ZelioX Custom	ZelioX Plus
<b>Battery capacity</b>					
Power	1600 Watts	1800 Watts	2500 Watts	3500 Watts	3500 Watts
Type	Lithium 12V	Lithium 24V	Lithium 24V	Lithium 24V	Lithium 24V
kWh	1.20 kWh	2.25 of 3.60 kWh	2.25 of 3.60 kWh	2.25 of 3.60 kWh	3.60 kWh
Ah	100	100 of 144	100 of 144	100	144
Chemistry	LifePO4	LifePO4	LifePO4	LifePO4	LifePO4
<b>Connections</b>					
230 V AC input	ZelioX Compact power cable	ZelioX shore power cable	ZelioX shore power cable	ZelioX shore power cable	ZelioX shore power cable
230 V AC output	1x AC power socket 1x IEC C19	2x AC power socket	2x AC power socket	2x AC power socket	2x AC power socket
112 V DC input	Anderson 50A	Anderson 175A	Anderson 175A	Anderson 175A	Anderson 175A
12 V DC output	Anderson 50A	Anderson 50A	Anderson 50A	Anderson 50A	Anderson 50A
<b>Product information</b>					
Weight (kg)	23	53 of 55	63 of 65	63	65
Dimensions (hxbxlm mm)	190x420x355	430x580x380	430x580x380	430x580x380	430x580x380
IP Rating	IP20	IP20	IP20	IP20	IP20
Working temperature range	0-50°C	0-50°C	0-50°C	0-50°C	0-50°C
Maximum temperature	70°C	70°C	70°C	70°C	70°C
Cooling	forced air	forced air	forced air	forced air	forced air
<b>AC Input</b>					
Voltage (V)	190-260	190-260	190-260	190-260	190-260
Frequency (Hz)	50	50	50	50	50
Charging capacity (W)	950	1250 of 1500	1250 of 1500	1250	1500
<b>AC Output</b>					
Voltage (V)	230 AC	230 AC	230 AC	230 AC	230 AC
Frequency (Hz)	50	50	50	50	50
Amp limit (A)	10	10	10	10	10
Continuous (W)	1300	2000	2800	2800	2800
10 minutes (W)	1600	2500	3500	3500	3500
10 sec peak (W)	2500	5500	6500	6500	6500
<b>DC Input</b>					
Voltage (V)	12-15 DC	12-15 DC	12-15 DC	12-15 DC	12-15 DC
Continuous power (A)	30	60	60	60	60
<b>DC Output</b>					
Voltage (V)	12	12	12	12	12
Amp limit (A)	25	25	25	25	25
Continuous (W)	300	300	300	300	300
Continuous power (W)	25	25	25	25	25
Maximum power (W)	35	35	35	35	35